



## Diamond SUPREME Step 3-N-1 Underlayment

Diamond SUPREME Step underlayment is a premium waterproof acoustical underlayment suitable for use under laminate, engineered hardwood, bamboo, wood, and most floating floor systems.

### PACKAGING

- Square footage per roll: 100
- Rolls per pallet: 42
- Item code: DSPAD

### TECHNICAL DATA

- Thickness: 3mm
- Length: 25'
- Width: 48"

### QUICK AND EASY INSTALLATION

**Requires no additional seaming tape, cuts with a knife.**

1. Install *Diamond Supreme Step* with foil side down against concrete/subfloor.
2. Roll out underlayment next to wall. Roll out next row in same manner butting underlayment close to first row (do not overlap) and covering the moisture barrier film. Tape the seam.
3. Install flooring according to the wood/laminate manufacturer's installation instructions.

Density: 3.5lbs per cubic foot

Fire resistance: UL 94 HFI. F.A.R. 25. 83

Water Absorption: 0.0015lbs per cubic foot

### SOUND ABSORPTION PROPERTIES

**IIC 78dB** (*Impact Insulation Class*) This method is to measure the impact sound transmission performance of a floor to ceiling assembly (transmission through the floor) with a 6" concrete slab with a suspended gypsum board ceiling.

**STC 79dB** (*Sound Transmission Class*) This method is to measure the air-borne sound insulating property of a partition element for effectiveness in blocking sound on a 6" concrete slab with a suspended gypsum board ceiling.

---

6903 Cypress Park Drive, Suite #100 ♦ Tampa, FL 33634 ♦ 813-609-4200

Orders@DiamondSurfacesandSupply.com