

QUIET WALK ELITE



PACKAGING									
PRODUCT DESCRIPTION	PCS/CTN	SF/CTN	SF/PLT	CTNS/PLT	DEPTH	PLT/CTNR	SF/CTNR	PLT SIZE	LBS/CTNR
7" x 48" - Luxury Vinyl Plank Acoustic Cushioning Embossed in Register (EIR) Painted Bevel	14	32.68	1797.19	55	5mm	20	35943.78	49"x40"x37"	51,280
PRODUCT					PERFORMANCE				
COLLECTION	AQUA SHIELD		TEST PERFORMED		ASTM		RATING		
CONSTRUCTION	LVP		IMPACT SOUND CONDUCTION		E492-09		62		
LOCKING SYSTEM	N/A		SOUND TRANSMISSION CLASS		E90-09		64		
WEAR LAYER	20 mil (.5mm)		SLIP RESISTANCE		D2047		>0.8 Low Risk		
THICKNESS	3.5mm + 1.5mm pad		DIMENSIONAL STABILITY		F2199		PASS <.02"/ft		
ATTACHED CUSHION	1.5mm pad		RESIDUAL INDENTATION		F1914		PASS		
INSTALLATION	Direct Glue Down		STATIC LOAD LIMIT		F970		PASS		
COLORS	St. Augustine, Vero Beach, Port St Lucie, Okeechobee, Punta Gorda		FLEXIBILITY		F137		PASS		
ENVIRONMENTAL			RESISTANCE TO HEAT		F1514		PASS		
INDOOR AIR QUALITY	UL Greenguard		RESISTANCE TO LIGHT		1515		PASS		
WARRANTY			RESISTANCE TO CHEMICALS		F925		5min - PASS	24hr - PASS	
RESIDENTIAL	25YRS		RADIANT FLUX		648		EXCEEDS CLASS 1		
LIGHT COMMERCIAL	20YRS		SMOKE DENSITY		E662		PASS		



WWW.DIAMOND-SURFACES.COM | WWW.AQUASHIELDFLOORING.COM

